AUDIBLE ALARMS


KPS-1500


ESB-6


KPS-124


KPS-100T
KPS-112


KPS-6000


KPS-104

Loud DC Sirens

Code	Volts	IP	dB	Tone	Rated Current	Colour
ESB-6	8-15VDC	55	100	Warble/Siren	200mA	● Black
KPS-1500	6-15VDC	65	105	Warble/Siren	300mA	● Black
KPS-112	6-14VDC	55	109	6 Tone	750mA	○ White
KPS-124	15-28VDC	55	106	Warble/Siren	90mA	● Black
KPS-100T	6-14VDC	55	115	1 Tone	1300mA	○ White
KPS-104	6-14VDC	55	102	Warble/Siren	750mA	● Black
KPS-6000	5-15VDC	65	105	Sweep	200mA	○ White

BACK-UP ALARMS


TK-428


AP-9805

Back-up Alert for Fork Lift

Code	Voltage	IP	dB	Tone	Rated Current	Colour
AP-9805	10-80VDC	65	97	Back-up	400mA	● Black
TK-428	6-12VDC	65	126	Back-up	650mA	● Black


TK438

Back-up Alert / Flasher Combination - 90 flashes/min

Code	Voltage	IP	dB	Tone	Rated Current	Colour
TK-438/R	6-12VDC	65	126	Back-up	800mA	● Red
TK-438/A	6-12VDC	65	126	Back-up	800mA	● Amber



Surface Mounting Back-up Alarm - IP67

Code	Voltage	Size (mm)	Db (1.2m)	Connector
PL-638	12-24VDC	86 x 100 x 41mm	97	Stud Terminals

- Surface mount alarm
- Offers a wide range of mounting options
- Rugged ABS housing provides durability
- Protected from vibration and moisture ingress



High Output Back-up Alarm - IP67


Code	Voltage	Size (mm)	Db (1.2m)	Connector
PL-8628	12-24VDC	85 x 101 x 49mm	107	Stud Terminals

- High level audio output
- Use for areas of high ambient noise
- Rugged nylon housing for durability
- Protected from vibration and moisture ingress
- Meets SAE J994 standards covering high pressure washing

PL-8668C



PL-628B



Smart Self-Adjusting Back-up Alarms - IP67

Code	Voltage	Size (mm)	Db (1.2m)	Connector
PL-8668C	12-24VDC	78 x 127 x 96mm	97 - 112	Stud Terminals
PL-628B	12-24VDC	78 x 127 x 96mm	77 - 102	Stud Terminals

- Monitors ambient background noise
- Automatically adjusts volume
- Rugged nylon housing for durability
- Protected from vibration and moisture ingress
- Meets SAE J994 standards covering high pressure washing

©ACDC Dynamics