

INSULATORS (1000V)

Polypropylene



Insulators




Type A, B, C	10mm	5mm	8mm
M/M	M10-MM-*	A5-MM-*	B8-MM-*
M/F	M10-MF-*	A5-MF-*	B8-MF-*
F/F	M10-FF-*	A5-FF-*	B8-FF-*


*Add colour to code: ● **R** *(Red)*, ● **BL** *(Blue)*, ○ **W** *(White)*, ● **BK** *(Black)*. *Eg.* **A5-MM-BL** *(Blue)*

Dough Moulded Compound (D.M.C)

Insulators



GL/GP




VL/VP

Type A, B, C	5mm	8mm	10mm	8mm
M/M	GL-5-*	GL-8-*	GL-10-*	VL-8-*
M/F	–	–	–	–
F/F	GP-5-*	GP-8-*	GP-10-*	VP-8-*

*Add colour to code: ● **R** *(Red)*, ● **BL** *(Blue)*, ● **BK** *(Black)*.

600V Transformer Bushings



Type A, B, C	6mm (45A)	8mm (60A)	10mm (80A)	12mm (120A)
M/M	B6	B8	B10	B12
M/F	–	–	–	–
F/F	–	–	–	–

Colour: Natural only.
Complete with gasket.
Brass Studs.

Dimensions: Polypropylene/DMC

CAT No.	A mm	B mm	C mm	E mm	F mm
A5	25	16	25	20	–
B8	41	22	40	25	–
M8	40	32	45	–	8
M10	40	32	45	–	10

Dimensions: D.M.C


CAT No.	A mm	B mm	C mm	E mm	F mm
G*-5	25	17	26	15	5
G*-8	42	25	45	25	8
G*-10	42	25	45	30	10
V*-8	40	30	50	25	8


*Add **L** or **P**


Dimensions

CAT No.	A mm	B mm	Cut Out mm	Stud
B6	85	28	15	M6
B8	95	30	21	M8
B10	110	33	22	M10
B12	120	35	24	M12

D.M.C. Insulators







10mm*	10mm*	12mm*	12mm*	16mm*
DJ10-MF-W	–	–	–	–
–	**DF10-FF-W**	**DF12-FF-W**	**DE12-FF-W**	**DD16-FF-W**

*Light Grey only

Dimensions

CAT No.	A mm	B mm	C mm	E mm	F mm
DJ10	50	40	45	30	10
DF10	50	35	45	–	10
DF12	50	35	45	–	12
DE12	60	45	60	–	12
DD16	60	45	60	–	16

DMC = Dough Moulded Compound Max. 187°C
All Insulators manufactured with Brass inserts and bright Zinc-plated steel studs where applicable.

Trolley Line (D.M.C)



Code	SM1000 (Light Grey)


Code	SM1000-BK (Black)
Height	55mm
Diameter	60mm
Hole/Stud	5/8" BSW

Code	SM2000
Height	65mm
Top Ø	50mm
Bottom Ø	72mm
Hole	M12

D.M.C with Flat Edge



SM-51 SM-35



SM-76

Code	SM-35	SM-51	SM-76
Volt withstand	10kV	15kV	25kV
Screw	8mm	8mm	10mm
Dimension:			
A	35mm	51mm	76mm
B	28mm	29mm	36mm
C	32mm	36mm	50mm

Available only in ● Red only

©ACDC Dynamics